





real-time



receive alerts when CO levels rise



monitor exposure over time

SPARROW Carbon Monoxide & Air Quality Monitor

for health, wellness, and safety

SPARROW is a smart phone connected carbon monoxide monitor for CO safety and air quality analysis. SPARROW and the SPARROW app work together to monitor CO in real-time and provide high level safety alerts and low-level air quality warnings.



SPARROW Preset Alert Levels


SPARROW provides an instantaneous alert. Go to settings to enable a TWA display.

		1 st Alert Level	2 nd Alert Level	3 rd Alert Level
Sensitivity Mode	Sensitive	9 ppm	15 ppm	25 ppm
	Default	15 ppm	35 ppm	70 ppm
	Home & Work	30 ppm	70 ppm	150 ppm
	Custom	0 – 50 ppm	0 – 200 ppm	25 – 400 ppm
Warning	SPARROW	 LED color change No audible alert 	- LED color change - Short audible beep	- LED color change - Long audible beep
	SPARROW App	- Display color change - No audible alert	- Display color change - Phone vibration - Danger warning	 Display color change Phone vibration Danger warning Text alert to emergency contact

*Phone alerts & TWA require app connection / Emergency Texting Feature requires app and data connection

Eco Sensors, a Division of KWJ Engineering, Inc. 8430 Central Avenue, Suite C Newark, CA 94560





Advanced features for Air Quality Analysis

PERFORMANCE SPECIFICATIONS			
CO Measurement Range	0 to 500 ppm		
CO Measurement Resolution	1 ppm		
CO Measurement Accuracy	± 4 ppm or 10% of value		
Temperature Sensor	-20 to 45 °C / -4 to 113 °F; 0.1 °C resolution		
Relative Humidity Sensor	0 to 100%; 0.1% resolution		
Water Resistant	Yes		
Battery Life	1+ weeks. Rechargeable via micro USB cable		
Data logging	SPARROW: 7 days of internal data logging in standalone operation. APP: Data logging to smart phone while paired.		
Alarm Indictors	SPARROW: Green, yellow, red, and purple LEDs & audible buzzer APP: Notifications with vibrate, sound, & emergency contact messaging		
Smartphone Connectivity	Bluetooth 4.1, iOS & Android Apps		
Operating Temperature Range	-20 to 45 °C / -4 to 113 °F		
Operating Humidity Range	15 to 95%		
Dimensions	61.2 x 32.0 x 9.9 mm / 2.41 x 1.26 x 0.39 in.		
Weight	< 2 Ounces		

Eco Sensors, a Division of KWJ Engineering, Inc. 8430 Central Avenue, Suite C Newark, CA 94560 **Built for**

otterbox uniVERSE